

TALON™ YELLOW GAS LINE PTFE TAPE

PROFESSIONAL HIGH DENSITY YELLOW PTFE TAPE

TGT-TAPE-SPEC

PRODUCT DESCRIPTION

PRODUCT

TALON™ YELLOW GAS LINE PTFE TAPE Professional High Density Yellow PTFE¹ Tape

DESCRIPTION

TALON™ YELLOW GAS LINE PTFE TAPE is a high density, all purpose, non-seizing, PTFE thread sealing compound in tape form that produces a leak-proof seal on all types of metal and plastic threaded connections. **TALON™ YELLOW GAS LINE PTFE TAPE** is a high density, 3.5 MIL PTFE. Its thickness allows for fewer wraps. Tape supplied on finished spools in an extra-long length.

RECOMMENDED USES

TALON™ YELLOW GAS LINE PTFE TAPE will not transfer any taste or odor to the system being sealed. Excellent for food and water systems. **TALON™ YELLOW GAS LINE PTFE TAPE** will never harden and is an anti-galling tape making it possible to disassemble pipes and bolts easily after years of service. Excellent for threaded stainless steel applications.

Chemically inert. It is suitable for use on systems carrying almost all types of chemicals and gases including:

Acids, Dilute	Hydraulic Oils
Alcohols	Hydrogen
Aliphatic Solvents	Inert Gases
Aromatic Solvents	Jet Fuel
Ammonia	Kerosene
Brine	Ketones
Compressed Air	Lacquer
Chlorinated Water	L P Gases
Coal Tar Naphtha	Mineral Oils
Cutting Oils	Naphtha
Diesel Fuel Oil	Natural Gas
Fatty Acids	Nitrogen Gas
Freon (All)	Petroleum Solvents
Gasohol	Propane
Gasoline	Soap, Liquid
Glycol	Steam Lines
Glycerin	Vegetable Oils
Heating Oils	Water
Helium	Xyloil

¹PolyTetraFluoroEthylene

TGT-TAPE SPEC

© 2025 J.C. Whitlam Manufacturing Company

COLOR/CONSISTENCY

The tape is yellow in color. It shall be free of visible voids, cracks, folds, contamination and has consistent physical properties. **TALON YELLOW GAS LINE PTFE TAPE** has an indefinite shelf life.

TEMPERATURE RANGE USE

Gases:

-450°F (-268°C) to 500°F (260°C)

Liquids:

-450°F (-268°C) to 500°F (260°C)

PRESSURE RANGE USE

Gases: up to 10,000 PSI (1450 kPa)

Liquids: up to 3,000 PSI (435 kPa)

The system may be pressurized immediately after assembly.

FOR USE ON THREADED

Galvanized steel, iron, brass, copper, aluminum, silicon bronze, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass.

CORROSIVENESS

TALON™ YELLOW GAS LINE PTFE TAPE is non-corrosive and prevents the corrosion and seizing of threads.

U.S. MILITARY AND INTERNATIONAL SPECIFICATIONS

TALON YELLOW GAS LINE PTFE TAPE meets MIL-T-27730A.

Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds.

Meets ANSI LC 7-2009 for Pipe Joint Sealing Compounds and Materials.

ENVIRONMENTAL STATEMENT

TALON YELLOW GAS LINE PTFE TAPE is chemically inert to virtually all environments. Non-Flammable.

TENSILE STRENGTH LONGITUDINAL
3000 PSI max - ASTM D882 (mod)

DENSITY / ELONGATION
0.8g/cm³ / 100%

THICKNESS
.0035 ± 10%

PACKAGING

U.S. Measure:

Stock Code	Size
Plastic Spool	
TGT1429	1/2" x 1429" (1.27 cm x 36.3 m)
TGTW1429	3/4" x 1429" (1.9 cm x 36.3 m)

SHIPPING WEIGHT PER CASE

Stock Code	Case Weight	#/Case
TGT1429	8 lbs. (3.6 kg)	45
TGTW1429	6 lbs. (2.7 kg)	27

DIRECTIONS FOR USE

1. Remove plastic spool.
2. Use 1/2" (1.27 cm) wide tape on fittings up to 1-1/2" (3.8 cm).
3. Wrap tape around the mail thread clockwise. Do not overlap the end of the fitting. Three wraps will seal most threads
3. Make up joint in a normal manner.

On large diameter pipe 4" (10.2 cm) and up, first wrap the pipe threads with two or more thicknesses of **TALON™ YELLOW GAS LINE PTFE TAPE** then apply **TALON™ THREAD SEALING COMPOUND** over the tape.



LISTED 4JPO

FOR USE IN THREADED JOINTS OF METAL PIPE (NOT EXCEEDING 1-1/2 IN. PIPE SIZE) IN ASSEMBLIES HANDLING GASOLINE, PETROLEUM OILS, PROPANE, BUTANE, NAPHTHA, BENZENE, KEROSENE, NATURAL GAS (NOT OVER 300 PSIG). A MINIMUM OF 3 WRAPS IS REQUIRED.



WHITLAM
The Industry Standard for Over 100 Years

P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@jcwhtlam.com
Website: www.talonptfe.com