

Eliminate Turbidity from the Start!

BLUE LUBE® PIPE GASKET LUBE

USES:

A blue viscous gasket lubricant for lubricating all rubber and plastic gaskets used in mechanical pipe coupling including Gruvlok® and Victaulic® type fittings. Blue Lube® insures proper alignment of gaskets for correct fit during pipe installation. It works well on wet or dry surfaces and is suitable for use on potable water systems. BLUE LUBE® is odorless and cleans up easily. Safe for use on all metal, plastic, and concrete pipe.

CONSISTENCY/COLOR:

Smooth, thixotropic
Lubricant/Blue

SPECIFICATIONS:

Meets NSF Standard 61

TEMPERATURE RANGE USE:

0°F (-17°C) to 150°F (66°C)

AVAILABLE SIZES

Stock#	Size
GLP4	1/4 Pint (118 ml)
GLP16	Pint (473 ml)
GLP32	Quart (.95 L)
GLP1	Gallon (3.785 L)
GLP5	5 Gallon (18.9 L)
GLP55	55 Gallon (208 L)



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada
Phone: 800-321-8358
FAX: 800-537-0588
International
Phone: 330-334-2524
FAX: 330-334-3005

www.blue-lube.info

© 2025 J.C. Whitlam Manufacturing Co.

BLUE LUBE® is an emulsified polymer based lubricant that is specially formulated to prevent turbidity, taste, and/or odor problems in new water main installations. Independent tests preformed by major municipalities have shown BLUE LUBE® will not promote turbidity, or transfer taste and odor, and completely flushes out of the system. BLUE LUBE® will not promote bacterial growth and is safe to use on all metal, plastic, and concrete pipe.



- Nontoxic
- Tasteless & Odorless
- Water Soluble
- Flushes Completely from the System
- Does Not Promote Bacterial Growth



Clean and Clear

BLUE LUBE® is clean, clear, tasteless and odorless. A sure, safe alternative to oleate based lubricants.



NSF Standard 61

Distributed By:



Typical Paste

BLUE LUBE® Paste



WHITLAM

The Industry Standard for Over 100 Years