

"Best stuff I ever used"



Leak Lock®

Pipe Joint Sealant

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon**, Cyclocac***, and all types of metal.

PRESSURE RANGE USE:

Full Vacuum:

Up to 10,000 PSI (703.0 Kg/cm²)

TEMPERATURE RANGE USE:

-200°F (-129°C) to +400°F (204°C)

U.S. FEDERAL SPECIFICATIONS

Leak Lock exceeds TT-S-1732

AVAILABLE SIZES

Stock#	Size
HS10001	2 oz. tube (56 g)
HS10004	1/4 pint (118 ml)
HS10016	1 pint (473 ml)

CURE TIME:

Leak Lock will cure and be ready for service in as little as 20 minutes or no more than 24 hours depending on pipe size and temperature of application.

*Dupont registered trademark

**Celanese registered trademark

***General Electric Plastics registered trademark

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282

U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005



www.joinpipe.com

© 2025 J.C. Whitlam Manufacturing Co.



- **All Metals**
- **All Plastics**
- **Silicone Free**
- **Non-Toxic**
- **Hydrocarbon Free**
- **Chemically Resistant**

Leak Lock is a state of the art high strength, pipe joint sealant consisting of chemically resistant film formers, plasticizers, reinforcing fillers and solvents. After joints are assembled, **Leak Lock** sets to form a chemically resistant flexible fluid-tight seal. Ideal

for joining dissimilar metals and other materials. **Leak Lock** is a proven formulation that will stick to all clean surfaces and can be used to prevent vibration from loosening nuts, bolts, plugs and fittings.

Suitable for use on systems carrying:

Acids, Dilute	Cyclohexane	Helium (Gaseous)	Natural Gas
Air, Compressed	Diesel Exhaust	Hydraulic Oils	Nitrogen (Gaseous)
Aliphatic Solvents	Fluid (DEF)	Hydrogen	Petroleum Solvents
Ammonia	Diesel Fuel Oil	Inert Gases	Propane
Aviation Fluids [†]	Fatty Acids	Isobutane	Refrigeration Gases [†]
Brine	Food Processing	Jet Fuel	Soap, Liquid
Butane	Freons (All)	(JP4, JP5, & JP6)	Steam Lines
Carbon Dioxide	Gasohol	Kerosene	Sugar, Liquid
Castor Oils	Gasoline [†]	LPG Gases	Vegetable Oils
Chlorinated Water	Glycerine	LNG	VM&P Naptha
Coal Tar Naptha	Glycol	Lacquer	Water (Potable)
Cutting Oils	Heating Oils	Mineral Oils	Xylol

Leak Lock should be applied to clean joint surfaces, either with the included applicator brush or any convenient spatula. Apply **Leak Lock** to both mating surfaces. Tack should be allowed to develop before joints are assembled.

Distributed By:

TRY:

Leak Lock GOLD
with PTFE



The Industry Standard for Over 100 Years

[†]Contact J.C. Whitlam Mfg. Company for compatible blends.