

RECOMMENDED USES:

Excellent for use on properly prepared interior or exterior surfaces of metal where a protective coating is desired. **TALON™ Direct to Metal (DTM) Enamels** provide a tough, durable finish that seals, beautifies and protects interior and exterior metal surfaces. Excellent for: piping, railings, drains, hydrants, flanges, grates, valves, backflows and most metal surfaces requiring a corrosion resistant coating.

PHYSICAL PROPERTIES:

Standard Colors: Red, Yellow, Blue, Gray, White, Green and Red Oxide. **Sheen:** 60+ at 60° - Gloss **Coverage:** 450 ft²/gal (40 m²/3.8L)

V.O.C.: Less than 400g/L

DRY TIME:

Handling: 4 - 6 Hours Recoat: 8 Hours

High humidity or low temperatures may increase dry time.

TEMPERATURE RANGE USE:

40°F (4°C) to 120°F (49°C)

APPLICATION: To be applied as is by brush, roller or spray. No thinning required.

CLEAN-UP: Mineral Spirits

PACKAGING (Metal Cans):

1 Gallon: 2 per case

J.C. Whitlam Manufacturing Co. P.O. Box 380 • Wadsworth, OH 44282



U.S. & Canada
Phone: 800-321-8358
FAX: 800-537-0588
International
Phone: 330-334-2524
FAX: 330-334-3005

www.TalonPaints.com Email: info@jcwhitlam.com

© 2025 J.C. Whitlam Manufacturing Co.

DIRECT TO METAL INDUSTRIAL ENAMEL

TALON™ DIRECT TO METAL (DTM) ENAMEL is a premium, industrial grade, alkyd enamel specially formulated for use on all types of metal surfaces. Its special rust-inhibiting formula creates an armor coating against the elements. TALON™ DTM ENAMEL coatings resist mild solvents, oils, mild chemicals and salt water. TALON™ DTM ENAMEL offers outstanding adhesion on properly prepared surfaces. Easy to apply by brush, roller or spray, TALON™ DTM ENAMEL provides excellent gloss retention and resistance to chalking and fading. TALON™ DTM ENAMEL is long lasting with maximum corrosion protection.







- Direct to Metal Coating
- Resists Corrosion
- Light Fast Colors
- Long Lasting Protection
- Tough Durable Finish

Standard Colors	Description	Stock Code	Size
	Bright Red	DTMRED1	1 Gal. (3.8L)
	Yellow	DTMYEL1	1 Gal. (3.8L)
	Blue	DTMBLU1	1 Gal. (3.8L)
	Machinery Gray	DTMGRAY1	1 Gal. (3.8L)
	Gloss White	DTMWHT1	1 Gal. (3.8L)
	Safety Green	DTMGRN1	1 Gal. (3.8L)
TALON™ Red Oxide Primer			
	Red Oxide	RO1	1 Gal. (3.8L)

Distributed By:

