

PRO-STRIPE

Traffic and Zone Marking Paint

PRODUCT DESCRIPTION

PRODUCT

PRO-STRIPE Traffic and Zone Marking Paint

99-2010 Traffic White
99-2115 Traffic Yellow
99-2125 Fire Lane Red
99-2135 Handicap Blue
99-2145 Line Covering Black

TYPE

Water-based Acrylic Latex. Organic Pigment

RECOMMENDED USE

A high-visibility, professional-grade paint formulated for crisp, durable line marking in traffic and safety applications. Excellent for use on asphalt or concrete; parking lots, roadways, crosswalks, stop zones, traffic patterns, pedestrian areas, storage zones, loading zones, and warehouses. Formulated **lead free** and **water soluble** for safe use and ease of application.

COLOR

Colors supplied as a premix in Yellow, White, Red, Blue, or Black. Do not tint.

SHEEN

Flat

PERCENT SOLIDS BY WEIGHT

99-2010 (White) - 48.5% \pm 2.0%
99-2115 (Yellow) - 38.5% \pm 2.0%
99-2125 (Red) - 36.9% \pm 2.0%
99-2135 (Blue) - 40.5% \pm 2.0%
99-2145 (Black) - 36.2% \pm 2.0%

PERCENT SOLIDS BY VOLUME

99-2010 (White) - 32.3% \pm 2.0%
99-2115 (Yellow) - 26.9% \pm 2.0%
99-2125 (Red) - 24.3% \pm 2.0%
99-2135 (Blue) - 28.6% \pm 2.0%
99-2145 (Black) - 28.0% \pm 2.0%

WEIGHT PER U.S. GALLON

White - 11.4 lbs. (5.2 kg) \pm 0.2 lbs. (91 g)
Yellow - 10.5 lbs. (4.8 kg) \pm 0.2 lbs. (91 g)
Red - 10.2 lbs. (4.6 kg) \pm 0.2 lbs. (91 g)
Blue - 10.3 lbs. (4.7 kg) \pm 0.2 lbs. (91 g)
Black - 9.8 lbs. (4.4 kg) \pm 0.2 lbs. (91 g)

TRAFFIC-SPEC

© 2026 J.C. Whitlam Manufacturing Company

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent, they are intended only as a source of information.

PERFORMANCE FEATURES

FEDERAL SPECIFICATIONS

Meets performance standards of Federal Specifications (GSA-FSS) TT-P-1952B Type 1.

APPLICATION DATA

SURFACE PREPARATION

Surfaces must be thoroughly clean before application. Remove any loose dirt, gravel, oil, loose paint, or foreign material. Patch large holes or surface cracks with an asphalt compound or concrete patch. Do not apply to wet surfaces or at temperatures below 50°F (16°C).

APPLICATION METHODS

Brush, roller, line marking machine, or spray (conventional and airless equipment).

APPLICATION EQUIPMENT

Brush: Polyester or nylon brush.

Roller: Use $\frac{1}{2}$ " nap roller cover or larger.

Marking Equipment:

Airless Spray and Conventional Spray: Non-specialized spray equipment in a wide range of sizes and types can be used.

VISCOOSITY

88-93 K.U. Krebs-Stormer Viscometer

THINNING

Thinning is not necessary; however, a small amount of water can be used to achieve proper spraying consistency.

DRYING TIME

77°F (25°C) and 50% relative humidity

To touch: 10 to 15 minutes*

No Tracking: 60 minutes

*This condition does not mean that the paint film has reached full cure; handling can be achieved without loosening, wrinkling, or otherwise marring the film under minimal pressure from fingers or hands. Drying times listed may vary depending on temperature, humidity, and air movement.

RECOMMENDED WET FILM PER COAT

Marking Machine: 15 mil
Brushing: 6 mil
Sprayed: 12 to 15 mil

RECOMMENDED DRY FILM PER COAT

Spray and Marking Machines: 6 to 7 mils
Brush: 3 to 4 mil.

RECOMMENDED SPREADING RATE

This material will cover 350 linear feet per gallon with a 4-inch line or 250 square feet per gallon.

CLEANUP

Best results use soap and warm water.

PACKAGING

U.S. Measure:
5-gallon (18.9 L) containers
55-gallon (208L) drums

FLASH POINTS

Water based formula.

Greater than 200°F (93°C) Pensky-Martens.

ENVIRONMENTAL STATEMENT

Pro-Stripe Traffic and Zone Marking Paint is an environmentally friendly formulation. Formulated to contain less than 0.06% lead in the dried film.

MADE IN U.S.A.

 **WHITLAM**
PAINT COMPANY
QUALITY COATINGS SINCE 1900

Division of

J.C. Whitlam Manufacturing Company

200 W. Walnut St. P.O. Box 380 Wadsworth, OH 44282

Phone: (330) 334-2524 or 1-800-321-8358